



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



Publication number:

**0 416 416 A1**

## EUROPEAN PATENT APPLICATION

Application number: **90116366.7**

Int. Cl.<sup>5</sup>: **C07K 1/14, C07K 5/02**

Date of filing: **27.08.90**

Priority: **04.09.89 IT 2161389**

Date of publication of application:  
**13.03.91 Bulletin 91/11**

Designated Contracting States:  
**AT BE CH DE DK ES FR GB GR LI LU NL SE**

Applicant: **SCLAVO S.p.A.**  
**Via Fiorentina 1**  
**I-53100 Siena(IT)**

Inventor: **Viscomi, Giuseppe Claudio**  
**Via Pietriccio-Belriguardo, 168**  
**I-53100 Siena(IT)**  
Inventor: **Cardinali, Franco**  
**Via Gaetano Ermoli, 18**  
**Localita' Tor tre Teste, I-00155 Rome(IT)**  
Inventor: **Longobardi, Maria Grazia**  
**Via Tor de' Schiavi, 130**  
**I-00172 Rome(IT)**

Representative: **Gervasi, Gemma, Dr. et al**  
**Studio Brevetti e Marchi NOTARBARTOLO &**  
**GERVASI 33, Viale Bianca Maria**  
**I-20122 Milano(IT)**

**Method for purifying low molecular weight compounds of peptide or pseudo-peptide structure.**

This invention firstly provides a method for purifying particular compounds of peptide or pseudo-peptide structure in which the number of protonable basic functions is greater than the number of acid functions and which have a molecular weight of less than 1000 daltons, by ion exchange displacement chromatography. In the method of the present invention the stationary phase used is a cationic exchange resin or a cross-linked polymer matrix activated with acid groups; the transporter solvent used is water if the compound to be purified already possesses at least one net positive charge, or aqueous dilute solutions of inorganic or strong organic acids which protonate the basic groups of the peptide or pseudo-peptide to be separated without modifying the structure of the peptide compound, such as acetic acid, trifluoroacetic acid, formic acid, hydrochloric acid or sulphuric acid; the displacer compound used is a triethylenetetraammonium salt.

**EP 0 416 416 A1**

1

5 net positive charges.

In other words, the peptides or pseudo-peptides which can be purified by the method of the present invention are those low molecular weight peptides or pseudo-peptides in which the balance between the protonable basic groups present in the side chain or in the terminal positions of the main chain and the acid groups also present in the side chain or in the terminal positions of the main chain is positive, and in particular those compounds in which the number of protonable basic groups exceeds the number of acid groups by 1, 2 or 3.

<sup>15</sup> analogues such as those described by J. Martinez and F. Winternitz in *Annals of the New York Academy of Sciences*, volume 419, 1983, and tuftsin retro-inverso peptide analogues of general formula (I)



R can be a  $-\text{CH}(\text{OH})\text{CH}_3$ ,  $-\text{CH}_2-\text{CH}_2-\text{S}-\text{CH}_3$  or  $-\text{CH}_2-\text{CH}(\text{CH}_3)_2$  group.

<sup>30</sup> R<sup>2</sup> is hydrogen or a metabolically labile acyl group,

Displacement chromatography is a chromatographic

35 station chromatography, and is characterised by the presence of a compound known as a displacer which must have the property of being more strongly adsorbed on the stationary phase than each component of the mixture to be separated or purified.

compound, even at high concentration. The mixture to be purified is thus fed into the column in a quantity such as to completely saturate the initial part of the column. A solution of the displacer compound is then pumped into the column until the stationary phase is completely saturated. During this latter stage the mixture components move along the column under the force of the displacer solution. More precisely, the more strongly adsorbed mixture components displace from the surface of the stationary phase those which have a milder interaction, until by this competitive adsorption mechanism a separation of the components is obtained in the form of adjacent bands of uniform concentration, the sequence of which depends on their degree of affinity with the stationary phase.

50 following: a greater quantity of purified product per unit of stationary phase; a high chromatographic yield; a reduced solvent consumption with consequent lower industrial costs; higher concentration of purified product in the eluate and thus easier product recovery from the effluent.

Displacement chromatography would therefore seem to be a method of extreme interest, mainly for separations on a preparative scale.

In particular, the application of this method in the biological field has been recently studied in terms of certain special aspects [see H. Kalasz et al., J. Chromatography, 215 (1981) p. 295 onwards; J.H. Frenz et al., J. chromatography, 330 (1985) p. 1 onwards; G. Vigh et al., J. Chromatography, 394 (1987), p. 305 onwards; G.C. Viscomi et al., J. Chromatography, 440 (1988), p. 157 onwards], and the purification of certain peptide compounds by reverse phase displacement chromatography has been described in detail.

The present invention firstly provides a method for purifying particular compounds of peptide or pseudo-peptide structure having a molecular weight of less than 1000 daltons and one, two or three net positive charges when in the protonated form, by ion exchange displacement chromatography. In the method of the present invention the stationary phase used is a cationic exchange resin or a crosslinked polymer matrix activated with acid groups. The transporter solvent used is water or aqueous dilute solutions of inorganic or strong organic acids which protonate the basic groups of the peptide or pseudo-peptide to be separated without modifying the structure of the peptide compound, such as acetic acid, hydrochloric acid or sulphuric acid. The displacer compound used is a triethylenetetraammonium salt. In this respect, the use of triethylenetetraammonium salts, the use of which as a displacer in displacement chromatography has never been described, has proved extremely advantageous in the purification of certain low molecular weight peptides and pseudo-peptides.

In practice, the column used is a conventional chromatography column, preferably a column for high resolution chromatography, packed with a stationary phase consisting of an organic or inorganic polymer activated with preferably strongly acid groups such as carboxylic or sulphonic groups, preferably in the form of small particles having a mean diameter of between 2 and 80  $\mu\text{m}$ , and more preferably between 5 and 50  $\mu\text{m}$ .

Once the operating conditions in terms of flow and concentration of the various species have been fixed for a given separation, the optimum column length for sharp separation of the mixture components depends on the quantity of substance to be purified. In this respect, the column must be of sufficient length to accommodate the isotachic sequence of adjacent bands.

When the column has been prepared, the chosen transporter solvent is water, if the peptide or pseudo-peptide to be purified is already in charged form, or inorganic or strong organic acid solutions if the peptide or pseudo-peptide is in neutral or not completely charged form, and depending on the solubility of the starting mixture in it and its capacity to elute the mixture components from the stationary phase, which must, as stated, be the lowest possible.

If acid solutions are used, the acid concentration is generally between 0.5 and 10 mmoles/litre and preferably between 1 and 5 mmoles/litre. The transporter solvent is firstly used to balance the column and then to dissolve the initial mixture to be purified.

The solution obtained is then diluted with the transporter solvent until it reaches an ionic force such as to allow its complete adsorption on the cationic exchange resin.

The ratio of quantity of mixture to be purified fed into the column to the volume of the stationary phase is kept between 10 and 100 mg/ml to prevent overloading of the column, which could result in incomplete separation.

When the solution containing the mixture to be separated has been prepared, this is fed into the column after which the solution of the displacer compound is pumped through the column, this compound in the purification method of the present invention being a triethylenetetraamine acid addition salt.

The optimum concentration of the displacer compound in the transporter solvent is typically between 1 and 100 mmoles/litre and preferably between 25 and 75 mmoles/litre, the linear flow rate with which this solution is passed through the column being maintained between 0.005 and 0.04 cm/sec.

The effluent is collected in fractions of suitable volume, the content of which is analyzed by conventional analytical methods. When analysis shows that the fraction contains the displacer compound the chromatographic run is suspended and the column regenerated if required. Regeneration is easily achieved by washing with aqueous solutions of acid salts having an ionic strength of at least 200 times that of the displacer solution, and then with water.

The advantages of the method of the present invention over the conventional linear elution methods are the reduced chromatography time, which is approximately about 1/2-1/3 of the time required for elution chromatography; the greater quantity of product loaded per ml of stationary phase (about 10 times greater); and the higher concentration of the purified product (10-100 times higher) in low salt concentration eluents, with consequent reduced recovery time and cost. The compound to be purified is collected in the form of a salt of acid addition, the counter-ion of which is that of the triethylenetetraammonium salt used as the displacer. If desired, the compound can be converted into the corresponding free base by known methods.

The purpose of the following example is merely to illustrate the process of the present invention in certain of its representative aspects, and must not be interpreted as representing a limitation on the scope

5

### Purification of [gThr<sup>1,m(R,S)</sup>Lys<sup>2</sup>]Tuftsin

10

15

20

## Claims

30

35



R is a  $-\text{CH}(\text{OH})\text{CH}_3$ ,  $-\text{CH}_2\text{CH}_2\text{S-CH}_3$  or  $-\text{CH}_2\text{CH}(\text{CH}_3)_2$  group.

45

50

55

10. The method of claim 1 wherein the displacer compound concentration in the transporter solvent is between 1 and 100 mmol/litre.

11. The method of claim 10 wherein the displacer concentration is between 25 and 75 mmoles/litre

5

10

15

20

25

30

35

40

45

50

55



European  
Patent Office

## EUROPEAN SEARCH REPORT

Application Number

EP 90 11 6366

### DOCUMENTS CONSIDERED TO BE RELEVANT

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
A	CHEMICAL ABSTRACTS, vol 71, 1969, page 78, abstract no. 120321t, Columbus, Ohio, US; R.L. MUNIER et al.: "Displacement chromatography of amino acids and their derivatives on ion exchange column with hydrophile support. II. Dansyl-amino acids and dansyl-peptides", & CHROMATOGRAPHIA 1969, (9), 386-92 * Abstract * -- -- --	1	C 07 K 1/14 C 07 K 5/02
A	CHEMICAL ABSTRACTS, vol. 105, no. 15, 13th October 1986, page 349, abstract no. 130288x, Columbus, Ohio, US; A. MUREL et al.: "Chromatophoresis: a new approach to the theory and practice of chromatofocusing. II. Experimental verification", & J. CHROMATOGR. 1986, 362(1), 101-12 * Abstract * -- -- -- --		
			TECHNICAL FIELDS SEARCHED (Int. Cl.5)
			C 07 K
The present search report has been drawn up for all claims			
Place of search	Date of completion of search		Examiner
The Hague	10 December 90		MASTURZO P.
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone		E : earlier patent document, but published on, or after the filing date	
Y : particularly relevant if combined with another document of the same category		D : document cited in the application	
A : technological background		L : document cited for other reasons	
O : non-written disclosure			
P : intermediate document		& : member of the same patent family, corresponding document	
T : theory or principle underlying the invention			